

U.S. DEPARTMENT OF LABOR  
Occupational Safety and Health Administration

Form Approved  
OMB No. 44-R1387

# MATERIAL SAFETY DATA SHEET

Dms 1824

Required under USDL Safety and Health Regulations for Ship Repairing,  
Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917) SEPTEMBER 1986

## SECTION I

MANUFACTURER'S NAME <b>Koppers Company, Inc.</b>		EMERGENCY TELEPHONE NO. <b>412- 227-2000</b>
ADDRESS (Number, Street, City, State, and ZIP Code) <b>Pittsburgh, PA 15219</b>		
CHEMICAL NAME AND SYNONYMS <b>ACRYLIC</b>	TRADE NAME AND SYNONYMS <b>Clear Gloss Lacquer</b>	
CHEMICAL FAMILY <b>ACRYLIC</b>	FORMULA <b>L-880-66 Clear</b> <b>DPM-86 and DPM-87</b>	

## SECTION II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS			BASE METAL		
CATALYST			ALLOYS		
VEHICLE <b>Acrylic</b>		<b>N/A</b>	METALLIC COATINGS		
SOLVENTS <b>See Below *</b>			FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS					
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES				%	TLV (Units)
<b>* Methyl Ethyl Ketone</b>					<b>200PPM</b>
<b>Methyl Isobutyl Ketone</b>					<b>50PPM</b>
<b>2-Propanol, 1 Methoxy Acetate</b>					<b>Not Established</b>

## SECTION III - PHYSICAL DATA

BOILING POINT (°F.)		SPECIFIC GRAVITY (H <sub>2</sub> O=1)	<b>lbs./Gal.</b> <b>7.50</b>
VAPOR PRESSURE (mm Hg.)		PERCENT VOLATILE BY VOLUME (%)	<b>84%</b>
VAPOR DENSITY (AIR=1)	<b>Heavier</b>	EVAPORATION RATE (N-But-Ace =1)	<b>Moderately Faster</b>
SOLUBILITY IN WATER	<b>Negligible</b>		
APPEARANCE AND ODOR			

## SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)	<b>24 F T.C.C.</b>	FLAMMABLE LIMITS	Let	Uel
EXTINGUISHING MEDIA	<b>Foam, dry chemical, water spray fog or CO .</b>			
SPECIAL FIRE FIGHTING PROCEDURES	<b>2</b> <b>Use air supplied equipment for enclosed areas. Cool exposed containers with water.</b>			
UNUSUAL FIRE AND EXPLOSION HAZARDS	<b>Keep away from heat, sparks and flame.</b>			

## SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE	50 PPM from solvent vapors in the air
EFFECTS OF OVEREXPOSURE	Systemic toxic effects may also result from skin absorption. Irritation to eyes, nose and throat near or above 50 ppm from vapors. Higher concentrations cause drowsiness, dizziness, followed by coma. Dangerously high concentrations could cause death from explosion or from breathing.
EMERGENCY AND FIRST AID PROCEDURES	If inhaled remove to fresh air. If not breathing give artificial respiration. preferably mouth to mouth. Call a physician. In case of skin contact, wash thoroughly with soap and water; for eyes, flush immediately with plenty of water for 15 minutes and call a physician. Wash contaminated clothing before reuse. If swallowed, CALL A PHYSICIAN IMMEDIATELY. DO NOT induce vomiting.

## SECTION VI - REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	
INCOMPATIBILITY (Materials to avoid)			
HAZARDOUS DECOMPOSITION PRODUCTS			
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	

## SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
Remove all sources of ignition (flames, electrical, static or frictional sparks, hot surfaces, etc.). Avoid breathing of vapors. Ventilate area. Contain and scoop up spills with non-sparking tools, rags, etc. Use inert absorbent materials on small spills or on residuals of large spills.
WASTE DISPOSAL METHOD
Dispose of in accordance with local applicable regulations.

## SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify type) Organic vapor canister where oxygen content is adequate and vapor concentration is less than 2% or use air supplied face masks.		
VENTILATION	LOCAL EXHAUST	SPECIAL
	MECHANICAL (General)	OTHER
PROTECTIVE GLOVES Neoprene Rubber Gloves		EYE PROTECTION Goggles
OTHER PROTECTIVE EQUIPMENT		

## SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING
Keep containers closed and upright to prevent leakage. Avoid flames, welding, smoking, sparks, open lights, etc. Avoid breathing of vapor or spray mist. Avoid eye and skin contact.
OTHER PRECAUTIONS
Maintain good personal hygiene. Do not use in confined areas, tank or pit without adequate ventilation.